



The Perfect Lift for your Perfect Home!

**Lift Models Suitable for
Villas / Bungalows / Independent Floor**





Model - Enduronic

Model - Mini Sukranti LR

Model - Eazy Ride

4 Persons

Lift Model	Load (Kgs)	Speed (MPS)	Stops / Travel	Car Inside (W x D)	Lift Shaft (mm) - Side Opening (W x D)	Lift Shaft (mm) - Centre Opening (W x D)	Pit Depth	Head-Room Height
Enduronic - Machine Room	272	0.66	7 stops / 18 meter	1100 x 750	1450 x 1400	1550 x 1350	1350	4100
Mini Sukranti (LR) - Machine Roomless	272	0.66	7 stops / 18 meter	800 x 950	1300 x 1250 ☹ ☹	1550 x 1250 ☹ ☹	1350	4000
Eazy Ride - Machine Roomless	272	0.2	3 stops / 9 meter	1000 x 1000	1650 x 1350	NA • 1 φ Power Supply	600	3000
				900 x 1150	1500 x 1500 ☹ ☹			

6 Persons

Lift Model	Load (Kgs)	Speed (MPS)	Stops / Travel	Car Inside (W x D)	Lift Shaft (mm) - Side Opening (W x D)	Lift Shaft (mm) - Centre Opening (W x D)	Pit Depth	Head-Room Height
Enduronic - Machine Room	408	0.66	7 stops / 18 meter	1100 x 1000	1500 x 1650	1550 x 1550	1350	4100
				1000 x 1100	1500 x 1750	1550 x 1650		
				1200 x 900	1600 x 1550	1750 x 1450		
Mini Sukranti (LR) - Machine Roomless	408	0.66	7 stops / 18 meter	1000 x 1100	1500 x 1350 ☹ ☹	1560 x 1350 ☹ ☹	1350	4000

8 Persons

Lift Model	Load (Kgs)	Speed (MPS)	Stops / Travel	Car Inside (W x D)	Lift Shaft (mm) - Side Opening (W x D)	Lift Shaft (mm) - Centre Opening (W x D)	Pit Depth	Head-Room Height
Enduronic - Machine Room	544	0.66	7 stops / 18 meter	1400 x 1000	1800 x 1650	1800 x 1550	1350	4100
				1300 x 1100	1700 x 1750	1800 x 1650		
				1200 x 1200	1600 x 1850	1750 x 1750		
Mini Sukranti (LR) - Machine Roomless	544	0.66	7 stops / 18 meter	1050 x 1350	1550 x 1650 ☹ ☹	1760 x 1600 ☹ ☹	1350	4000
				1100 x 1300	1600 x 1600 ☹ ☹	1760 x 1550 ☹ ☹		

☹ Front entrance wall thickness 180mm required for Centre Opening Door	☹ Front wall recess 50mm required for Centre Opening Door
☹ Front entrance wall thickness 140mm required for Side Opening Door	☹ Front wall recess 90mm required for Side Opening Door

Note: All dimensions are in millimeters. All dimensions are clear finished lift shafts after plastering. Lifting hook in headroom required. RCC headroom structural slab 150 thick designed to sustain minimum 1000 kg/m² UDL. For specific requirements our local representative will be happy to work with you in preparation of the drawings. Specifications are subject to change without prior notice.

Landing Door



Glass Door (Optional)

Cabin (Optional)



SS Hairline

Landing Operating Panel



JLLP02 - Surface Mounted
Enduronic | Mini Sukranti LR

Hand Rail



JLHR01 - Round Handrail
Enduronic | Mini Sukranti LR | Eazy Ride

Ceiling options



Enduronic



Mini Sukranti LR



Eazy Ride

Car Operating Panel



Enduronic



Mini Sukranti LR



Eazy Ride

OVERSEAS

NORTH

Chandigarh, Gurgaon,
Delhi, Jaipur, Jammu,
Lucknow, Noida

EAST

Bhubaneswar, Guwahati,
Kolkata, Patna, Ranchi



CENTRAL

Amaravati, Bhopal,
Indore, Jabalpur, Nagpur,
Nashik, Raipur

WEST

Ahmedabad, Goa, Kolhapur,
Mumbai Andheri, Mumbai Mahpe,
Pune, Solapur, Surat, Vadodara

SOUTH

Bengaluru, Calicut, Chennai,
Chidambaram, Cochin, Coimbatore,
Hubli, Hyderabad, Madurai, Mangalore,
Mysore, Puducherry, Salem, Tirunelveli,
Tirupathi, Trichy, Trivandrum, Vellore,
Vijayawada, Vishakapatnam

4 Factories | 70 Branches in India | 7 Offices Overseas | 9,000+ Employees



Scan to visit our website



Johnson Lifts Private Limited

Corporate Office: 1, East Main Road, Anna Nagar Western Extn., Chennai 101
Ph: +91-44-26152200 | info@johnsonliftsltd.com | www.johnsonliftsltd.com